



THERMAKRAFT

MFG. LIMITATIONS

	Width
Minimum	*
Maximum	48"

	Height
Minimum	*
Maximum	77"

* Minimum width and heights are determined by process machinery capabilities.

BASELINE PERFORMANCE

Thermal Insulation

GLASS	Uc Value	R Value
Low-E/Argon/Dual	.27	3.70
Low-E/Argon/Triple	.22	4.55
Low-E/Krypton/Triple	.19	5.26

Structural Performance

Air Infiltration@ 25MPH	.04 cfm/ft ²
Water Penetration	5.25 psf
Uniform Loads	+/-52.5 psf

AAMA RATING: H-R35

FEATURES & BENEFITS

- Exterior colonial flat face look.
- Equal & unequal glass versions.
- Grade 35 performance.
- Sloped sill and sill insert configurations available.
- 1" glass capability.
- Exterior glazed sash.
- Long reach interlock. No colliding or missing.
- Double wall frame for less roll.
- Dual weatherstripping.
- Universal pivot shoe pocket, Spiral, Block & Tackle, and Constant force balance option.
- Full family of Double Hung, Double Slider, and Picture Window.
- Accessory options for Bay applications.
- Full and half screen options.
- Accessory grooves for slide on nail fin for new construction application.
- Optional dual-walled lift and pull rails available.

ASSEMBLIES

