




REPLACEMENT WINDOWS

the CORE PW30W PICTURE WINDOW

Window & door platform products by VEKA



PW3001
COMMON FRAME



BV56
1" BEAD

THERMAKRAFT



MFG. LIMITATIONS

Minimum	*
Maximum	40 ft ²

* Minimum sizes are determined by process machinery capabilities.

BASELINE PERFORMANCE

Thermal Insulation

GLASS	Uc Value	R Value
Low-E/Argon/Dual	.27	3.70
Low-E/Argon/Triple	.22	4.55
Low-E/Krypton/Triple	.19	5.26

Structural Performance

Air Infiltration@ 25MPH	.01 cfm/ft ²
Water Penetration	7.50 psf
Uniform Loads	+/- 75.0 psf

AAMA RATING: CW-PG50-FW

FEATURES & BENEFITS

- Grade 50 performance.
- Exterior frame bevel.
- All Welded, Brickmold, sloped sill, brickmold look J-channel.
- 3/4" glass capability or 5/8".
- Exterior glazed.
- Double wall frame for less roll.
- No sill tower notch at integral mull.
- Strong integral mull reinforcement.
- Optional two piece field mulling system.
- Full family of Double Hung, Double Slider, and Picture Window.

ASSEMBLIES

